

WWW.RAYMAC.BIZ

SALES@RAYMAC.BIZ TOLL FREE: (800) 890-3243 LOCAL: (586) 716-9164

FAX: (586) 273-3209

Name:			Comp	any:		
Phone:		E-mai	il:			
Job Name & lo	cation:					
1) Please disconnect all power to unit before carefully removing the cover. $\frac{1}{2}$						
•		sleeve dimension n diagram to the	•	g from outside ed	dge	A
A (Width)=	dth)= B (Height)=			C (Depth)=	
3) Power connection: □ Wall outlet plug □ Hardwired		rmored cable	☐ Hardw	☐ Hardwired electrical sub base		
4) Voltage:	□ 115 volt	□ 208/230 volt		volt		☐ 265/277 volt
5) Amperage:	□ 15 amp				□ 30 amp	
	ural gas eat	☐ Heat pump (☐ Straight cool			ater	
		or steam heat ple ormally open		e valve and the valve normally clo		below:
Voltage: ☐ Line Voltage			□ 11.	☐ 115 Volt		☐ 24 Volt
7) More inform	nation about	the unit(s) to be	replaced:			
Brand: _						
Model #	:					
Minimun	n circuit amp	acity:				
Approxir	mate age of	the unit(s) or seri	al #:			
9) BTU Capacit	y: Cool:		_ Heat:			
10) Age of the	units (or serie	al number):				_
11) What type	of wall const	ruction exists (Ex	: glass, masonr	y, metal frame, v	wood fro	ıme, panel):
12) Wall depth	(finished inte	erior to finished e	xterior):			
13) How is the unit controlled? ☐ Unit mounted thermostat ☐ Remote wall mount thermostat						
14) If a power of it from the	cord exists, p ne following:	olease select			,	The NEMA 6-30R is the same shape as 6-15R